

H800 CLASS MV FAIRLANE



SPECIFICATIONS

Call sign:	PBFW	Number of holds:	1
IMO no.:	9153654	Number of hatches:	1
Port of registry:	Rotterdam	Bale capacity (with tweendecks in holds)	
Flag:	Netherlands	abt.:	10,977 m3
Classification:	Lloyd's Register +100 A1, strengthened for heavy cargoes, bottom strengthened for loading / unloading	Free deckspace abt.:	1,500 m2
	aground CG, LMS, UMS, SCM	Hold: dimensions lowerhold:	58.65 x 15.18 x 7.28 m
Built:	2001	Hold: dimensions tweendeck:	72.75 x 15.18 x 4.09 m
Owner:	Fairlane B.V.	Hold: total height:	12.17 m
General agent:	Kahn Scheepvaart B.V.	Strength of tanktop:	12.00 t/m2
Owners P.I. club:	Gard A.S. Arendal, Norway	Strength of tweendecks:	4.25 t/m2
Deadweight (summer) abt:	7,051 t all told	Strength of hatchcovers:	4.25 t/m2
Draft (above bottom of keel):	7.72 m	Number of tweendecks:	1 (flush) adjustable in height
Length o.a.:	110.49 m	Cargo gear:	2 cranes each 400 t / combined 800 t
Beam o.a. (hull):	20.85 m		Auxiliary hoist 2 x 25 t
Air draft (above keel, jibs & derricks down):	36.40 m	Main engine(s):	MAN/B&W 7S 35MC, 4,900 kW
G.T.:	7,971 t	Thrusters:	Bowthruster: Lips, 610 kW
N.T.:	2,391 t	Speed about:	14.50 knots
G.T. Suez Canal:	8,116 t	Bunker capacity:	800 t HFO 380/115 t MGO
N.T. Suez Canal:	6,723 t	Fresh water capacity:	167.00 t
G.T. Panama:		No. insulated cargo spaces:	
N.T. Panama:	6,744 t	No. cargo tanks:	
		Container intake (sub weight):	340 TEU
			Lakes fitted

HAVENSTRAAT 23
3115 HC SCHIEDAM
THE NETHERLANDS
PHONE +31 10 79 00 300
INFO@JUMBOMARITIME.NL

